



Bearing NO.	Type	Dimensions ( in. /mm )						Dynamic load ratings (N)	Static load ratings (N)	Weight (kg)
		d <sub>1</sub>	H	D	C	B	h			
GW208PPB5	2	1.2598	1.1800	3.1490	0.9450	1.4370	0.2520	29500	18100	0.635
		32.00	29.97	80.00	24.00	36.50	6.40			
GW208PPB6	2	1.0945	1.0300	3.1490	0.9450	1.4370	0.2520	29500	18100	0.762
		27.80	26.16	80.00	24.00	36.50	6.40			
GW208PPB8	2	1.2598	1.1800	3.1490	0.9450	1.1890	0.2520	29500	18100	0.658
		32.00	29.97	80.00	24.00	30.20	6.40			
GW209PPB5	2	1.3504	1.2900	3.3465	1.1890	1.4370	0.2598	32700	20900	0.795
		34.30	32.77	85.00	30.20	36.50	6.60			
GW209PPB8	2	1.3504	1.2900	3.3465	0.8661	1.4370	0.2598	32700	20900	0.749
		34.30	32.77	85.00	22.00	36.50	6.60			
GW209PPB17	2	1.2600	1.1800	3.3155	1.1890	1.4370	0.2598	32700	20900	1.922
		32.00	29.97	85.74	30.20	36.50	6.60			
GW210PPB4	1	1.2598	1.1800	3.5433	1.1890	1.1890	0.2598	35000	23200	0.840
		32.00	29.97	90.00	30.20	30.20	6.60			
GW211PP3	4	1.6535	1.5311	3.9370	1.3126	1.3126	0.2992	43300	29200	1.106
		42.00	38.89	100.00	33.30	33.30	7.60			
GW211PPB3	1	1.6535	1.5311	3.9370	1.3126	1.3126	0.2992	43300	29200	1.036
		42.00	38.89	100.00	33.30	33.30	7.60			
GW211PP5	3	1.6535	1.5311	4.0000	1.4370	1.7500	0.2992	43300	29200	1.302
		42.00	38.89	101.60	36.50	44.45	7.60			
GW211PP17	3	1.6535	1.5311	3.9370	1.3126	1.7500	0.2992	43300	29200	1.252
		42.00	38.89	100.00	33.30	44.45	7.60			
GW214PPB4	1	2.1610	2.0550	4.9213	1.5630	1.5630	0.3543	62100	44800	2.157
		54.90	52.20	125.00	39.70	39.70	9.00			